



BAHIA



La sospensione di forma circolare è realizzata in estrusione di alluminio verniciato. Colori disponibili bianco e nero opaco. Lo schermo in PMMA garantisce l'emissione ottimale dei flussi luminosi emessi dalla scheda LED. L'apparecchio è regolabile in altezza attraverso i 3 cavi in acciaio con sistema meccanico di fissaggio (grip-lock). Il driver, ad alta efficienza, è integrato nel rosone a soffitto. Sono disponibili versioni dimmerabili multifunzione con controllo 1...10V, Push, DALI.

The circular suspension is made of painted aluminum extrusion. Available colors white and matt black. The PMMA screen guarantees the optimal emission of LED board luminous fluxes. The device is adjustable in height through the 3 steel cables with a mechanical fixing system (grip-lock). The high efficiency driver is integrated in the canopy. Multifunction dimmable versions with 1... 10V, Push, DALI.



Optical Info p. 535

Description	Colour	Power	Source	Lumen Output	CCT	Weight	Code
Ø 60_ On / Off	White	40 W	SMD LED	2650 lm	3000K	3,0 kg	GRF16111
	Black	40 W	SMD LED	2650 lm	3000K	3,0 kg	GRF16112
Ø 80_ On / Off	White	60 W	SMD LED	3100 lm	3000K	4,0 kg	GRF16113
	Black	60 W	SMD LED	3100 lm	3000K	4,0 kg	GRF16114
Ø 60_ DALI / 1...10 V / Push	White	40 W	SMD LED	2650 lm	3000K	3,0 kg	GRF16111DM
	Black	40 W	SMD LED	2650 lm	3000K	3,0 kg	GRF16112DM
Ø 80_ DALI / 1...10 V / Push	White	60 W	SMD LED	3100 lm	3000K	4,0 kg	GRF16113DM
	Black	60 W	SMD LED	3100 lm	3000K	4,0 kg	GRF16114DM

 220÷240Vac | IP20

Versioni dimmerabili: regolazione della luminosità 0/1 - 100 % - Dimmable versions: light regulation 0/1 - 100 %

Finishes

White

Black

