

### 1.0 LED

LED COB 6/9W | 350/500mA | 17V  
excl. driver  
aluminium powder coated

IP20 0°-35°/355° A 36° SDCM2 L80/55K 0.17kg

wire springs 86-89 90 4-23

CODE
184361W_
184361S_
184361M_
184361G_
184361Q_
184361B_

blade springs 86-89 90 min 6

CODE
184361W_C
184361B_C


LIGHT COLOUR	LUMEN   CRI	CODE
2700K	530/715   >90	3
3000K	575/775   >90	5
4000K	620/830   >90	7
2000-3000K	380/560   >90	9

### ALWAYS USE

driver | 500mA

	CODE
10W	90214405
10W dim	90224402
20W DALI	90244604

more options and specs on page 737



### 1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V  
excl. driver  
aluminium powder coated

IP20 0°-35°/355° 0.17kg

wire springs 86-89 90 4-23

CODE
112310W0
112310S0
112310M0
112310G0
112310Q0
112310B0

blade springs 86-89 90 min 6

CODE
112310W0C
112310B0C

### ALWAYS USE

driver | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

specs on page 739

# DEEP ADJUST

## CEILING RECESSED



### 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

IP20 0°-35°/355° 0.21kg

wire springs 86-89 105 4-23

CODE
112320W0
112320S0
112320M0
112320G0
112320Q0
112320B0

blade springs 86-89 105 min 6

CODE
112320W0C
112320B0C

### OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K   460lm	901228W3
2700K   437lm	901228B3
3000K   500lm	901228W5
3000K   457lm	901228B5

more lamps and specs on page 743

