




DEEP IP44 | IP65

CEILING RECESSED



1.0 LED

LED COB 6/9W | 350/500mA | 17V
excl. driver
aluminium powder coated

IP65 33° SDCM2 L80/55K 0.24kg

wire springs 86-89 90 4-27

CODE	
184161W_	184161B_

blade springs 86-89 90 min 4

CODE	
184161W_C	184161B_C

LIGHT COLOUR	LUMEN CRI	CODE
2700K	485/640 >90	3
3000K	510/690 >90	5

ALWAYS USE

driver | 500mA

CODE	
10W IP20	90214405
10W IP20 dim	90224402
24W IP68	90214702

more options and specs on page 737



1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V
excl. driver
aluminium powder coated

IP44 0.15kg

wire springs 86-89 90 4-25

CODE	
112610W0	112610B0

blade springs 86-89 90 min 8

CODE	
112610W0C	112610B0C

ALWAYS USE

driver | 12V

CODE	
10W dim	90221401
25W dim	90221701
70W dim	90221904

specs on page 739



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP44 0.16kg

wire springs 86-89 105 4-25

CODE	
112620W0	112620B0

blade springs 86-89 105 min 8

CODE	
112620W0C	112620B0C

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

CODE	
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5

more lamps and specs on page 743

