

SLIM_Semirecessed



Slim semi_incasso è parte integrante della collezione assieme alla versione track e parete. Diverse le scelte possibili all'interno della gamma: potenze di 12W, 20W, 33W; schede led con tono colore 2700, 3000 e 4000K; ottiche con diverse angolazioni unitamente ad una paletta colori allargata ampliano i valori della proposta e le possibilità d'installazione. La luce emessa si distingue per l'ottima diffusione del fascio e per l'elevata qualità cromatica (CRI > 90 / MacAdam < 3). Queste caratteristiche li rendono particolarmente adatti all'illuminazione di negozi, delle aree espositive e di tutti quegli ambienti dove la resa del colore e la pulizia dei fasci luminosi sono di primaria importanza. Le lenti ottiche intercambiabili sono di tipo semidiffusivo e l'abbagliamento diretto è totalmente controllato grazie alla profonda schermatura con un cut-off di 36° che caratterizza il frontale. Oltre alle tradizionali versioni On/Off, Slim è disponibile anche nelle versioni con alimentazione DALI e Casambi. Il driver è separato dall'apparecchio e viene inserito nel controsoffitto attraverso il foro di fissaggio.

Slim semi_incasso is an integral part of the collection, along with the track and wall versions. There are various choices available within the range: power options of 12W, 20W, 33W; LED boards with color temperatures of 2700K, 3000K, and 4000K; optics with different angles, along with an expanded color palette, enhance the proposal value and installation possibilities. The emitted light is distinguished by excellent beam diffusion and high color quality (CRI > 90 / MacAdam < 3). These features make them particularly suitable for lighting shops, exhibition areas, and all environments where color rendering and clean light beams are of primary importance. The interchangeable optical lenses are semi-diffusing, and direct glare is completely controlled thanks to the deep shielding with a 36° cut-off that characterizes the front. In addition to the traditional On/Off versions, Slim is also available in DALI and Casambi power supply options. The driver is separate from the fixture and is inserted into the false ceiling through the mounting hole.



+ SLIM GU10 Track pag 198



+ SLIM Track pag 192




EXTENDED
COLLECTION



+ SLIM GU10 Ceiling pag 251

+ SLIM Ceiling pag 248

SLIM_Semirecessed



Power	Lumen output	Hole size	Product dimension				Weight	*code to complete
			A	B	C	D		
12W	1255 lm	70 mm	85 mm	134 mm	183 mm	52 mm	0,39 kg	TB-CA ☉ ● □ :: ▼
20W	2280 lm	70 mm	85 mm	150 mm	187 mm	55 mm	0,49 kg	TB-CC ☉ ● □ :: ▼
33W	3486 lm	70 mm	85 mm	140 mm	180 mm	72 mm	0,61 kg	TB-CE ☉ ● □ :: ▼

☐ 220÷240Vac | IP20

CRI>90 | RG1 | SDCM<3

UP to 114 lm/W | L80/B20 50.000 h.

Lumen output values: luminaire luminous flux at 4000 K - optics 38°

Optical Info p. 533

* Select your option


Colour Base	CCT	Optic	Control	Colour
White W	2700 K 1	15° 1	On/Off NF	White W
Black B	3000 K 2	24° 2	Phase Cut** PC	Black B
	4000 K 3	38° 4	Push PU	Sand V
		55° 5	0-1/10 V AN	Silver G
			DALI DA	Tobacco O
			Casambi CA	

** only: 12W - 20W

SLIM_GU10 Semirecessed



GU10



Power	Source	Hole size	Product dimension				Weight	*	code to complete
			A	B	C	D			
1x max 50W	GU10	70 mm	85 mm	110 mm	161 mm	55 mm	0,25 kg		TC-C ▼
<input type="checkbox"/> 220÷240Vac IP20									
Lamp not included									

* Select your option

Colour ▼

- White W
- Black B